

## SECURE SWITCHING FOR DOWNLOADING NETWORK BOOTS

### BACKGROUND OF THE INVENTION

#### 1. Technical Field

[0001] The present invention relates in general to the field of computers, and in particular to multiple blade servers housed in a server chassis. Still more particularly, the present invention relates to a method and system for filtering, through an Ethernet switch, responses from Dynamic Host Configuration Protocol (DHCP) servers to a blade server's network boot request, such that responses to the network boot request are only accepted from trusted DHCP servers.

#### 2. Description of the Related Art

[0002] Server blade computers offer high-density server boards (blades) in a single chassis (blade chassis). Server blades are servers that often are under at least partial control of a primary server, having a relationship similar to that of a server/client. Thus, as shown in Figure 1, a blade chassis **102**, having multiple server blades **103**, is connected to a network **106**, which also connects to multiple clients **104**.

[0003] One of the server blades **103** may utilize a network boot protocol known as Pre-boot Execution Environment (PXE). PXE allows server blade **103** to request an Internet Protocol (IP) address from the DHCP server **108**, and to obtain the IP address of a PXE boot program server, from PXE boot server network **110**, that can provide a boot image that can be used to load a new operating system (OS), flash a Basic Input/Output System (BIOS) memory, or even erase data on a local hard disk. Management server network **108**, typically comprised of Dynamic Host Configuration Protocol (DHCP) servers, and PXE boot server network **110**, are connected to blade chassis **102** via network **106**.

[0004] To download a boot program, server blade **103** broadcasts a request to network **108**. One or more of the DHCP servers in network **108** respond back to server blade **103** with a

dynamic IP address along with lease information and a list of PXE Boot S servers from network **110** that can download a boot program to server blade **103**. If responses from multiple DHCP servers from network **108** are put on network **106**, then server blade **103** typically responds to the first request response to arrive a server blade **103**.

**[0005]** A network boot of server blade **103** as described is not secure, since the broadcasted boot request can result in a response from any DHCP or PXE server connected to network **106**, including an unauthorized DHCP server attempting to tamper with the network. For example, an unauthorized DHCP server could direct server blade **103** to an unauthorized PXE boot server, which could result in possible undesired operation such as exposures to operational security and/or destroying data on a local fixed disk drive. What is needed, therefore, is a method and system for preventing booting from unauthorized DHCP/PXE servers.

## SUMMARY OF THE INVENTION

[0006] The present invention is directed to a method and system for managing a secure network boot of a server blade. The server blade is part of a server blade chassis, which holds multiple server blades that communicate with outside devices via an Ethernet switch, which is under the control of a management module in the server blade chassis. The management module oversees communication between server blades and networks of multiple Dynamic Host Configuration Protocol (DHCP) servers and Pre-boot Execution Environment (PXE) boot program servers. When a server blade receives a response from a DHCP server directing the server blade to a PXE boot program server, the Ethernet switch compares the identity of the responding DHCP server with a list of trusted DHCP servers. Only if the responding DHCP server is on the list of trusted DHCP servers and the PXE Boot Server information it provides is on the list of trusted PXE Boot Servers will the Ethernet switch allow the server blade to access and download a boot program from a PXE server suggested by the DHCP server.

[0007] The above, as well as additional objectives, features, and advantages of the present invention will become apparent in the following detailed written description.

## BRIEF DESCRIPTION OF THE DRAWINGS

[0008] The novel features believed characteristic of the invention are set forth in the appended claims. The invention itself, however, as well as a preferred mode of use, further purposes and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with the accompanying drawings, where:

[0009] **Figure 1** depicts a prior art diagram of a network connecting a server blade computer (blade chassis) with primary servers;

[0010] **Figure 2** illustrates a blade chassis incorporating a trusted DHCP server list and a trusted PXE Boot Server list in a management module in the blade chassis;

[0011] **Figures 3a-b** depict a flow-chart of the present invention's method for a server blade to acquire a boot program and Internet Protocol (IP) address from trusted Dynamic Host Configuration Protocol (DHCP) servers; and

[0012] **Figure 4** illustrates a boot program network using different formats of Pre-boot Execution Environment (PXE) servers.

## DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT

[0013] With reference now to **Figure 2**, there is depicted a schematic block diagram of a server blade chassis **200** according to a preferred embodiment of the present invention. For the sake of clarity, only one management module **202** and three server blades **204** are depicted. However, in a preferred embodiment, a backup management module **202** is incorporated into server blade chassis **200**, and server blade chassis **200** has a midplane capable of connecting several server blades **204**.

[0014] Management module **202** is coupled to server blades **204a-c** via a midplane **210**, which contains at least one serial bus for secure internal communication between management module **202** and server blades **204a-c**, as well as between server blades **204a-c** themselves, via respective service processors **208a-c**. Management module **202** also communicates with an Ethernet switch via an internal secure serial bus **216** to control communication between DHCP/PXE Boot servers and server blades **204** as described below.

[0015] Management module **202** has the capability of sending alerts to administrator server **222** to indicate changes in server blade chassis **200**'s status, such as a removal or addition of a blade **204**. Management module **202** can detect the presence, quantity, type and revision level of each server blade **204**, power module **212**, cooling fans **214**, and midplane **210** in the system, and can detect invalid or unsupported configurations. If a problem is detected in any part of the system, management module **204** can transmit a warning to administrator server **222** via Ethernet switch **216**.

[0016] Each server blade **204** has at least one central processing unit (CPU) **206**, and a non-volatile memory (NVM) **226**. Each server blade **204** communicates with an external network **230** via a Network Interface Card (NIC) **240** and an Ethernet switch **216**. For the purpose of clarity, only one Ethernet switch **216** is shown, although in a preferred embodiment server blade chassis **200** has at least two Ethernet switches **216**, whose communication with each server blade **204** is coordinated by a management module **202** which consults a blade present table **224** associated with each Ethernet switch **216**.

[0017] Management module **202** manages and coordinates communication between server blades **204** and network **230** via Ethernet switch **216** and administrator server **222**. In a preferred embodiment, communication is directly between Ethernet switch **216** and network **230**. As described in detail in **Figure 3**, management module **202** also maintains a trusted DHCP server list **218** and a trusted Boot server list **219**.

[0018] With reference now to **Figure 3**, there is depicted a flowchart of a preferred embodiment of the present invention's method for securely obtaining a network boot program for a server blade. As shown at block **300**, the server blade is powered up and a power on self-test (POST) program is run, performing basic system testing. To initiate the process of a network boot (as opposed to booting from a local device such as a hardfile), the server blade sends a DHCP DISCOVER request to a network of DHCP servers (block **302**), which are preferably DHCP servers (management servers) capable of returning to the server blade a Dynamic IP address and the IP address of a PXE Boot Server that is capable of downloading a boot program to the server blade. One or more DHCP servers respond with DHCP OFFER messages back to the Ethernet switch used by the requesting server blade (block **304**). The DHCP OFFER messages contain the IP addresses of the responding DHCP servers, a Dynamic IP address with lease information (preferably as defined by the Internet Engineering Task Force Request For Comments 1534, 2131, and 2132), plus a list of PXE Boot Servers that the server blade can contact to download a boot program.

[0019] When the Ethernet Switch receives the selected DHCP OFFER message from the responding DHCP server, a determination is made as to whether the responding DHCP server is trustworthy and whether the boot server to which the offer refers is trustworthy (block **306**). This determination is accomplished by Ethernet Switch **216** filtering the responses by looking for DHCP OFFERs that are contained within the list of trusted boot servers **219** list programmed into the Ethernet Switch. In a preferred embodiment, this comparison is made by evaluating the responding DHCP server's packets at Layer 3 of the Open Systems Interconnection (OSI) model. As known to those skilled in the art, upper OSI layers 7 through 4 support Application,

Presentation, Session and Transport respectively, while lower OSI layers 2 and 1 support Data Link and Physical levels respectively. OSI layer 3 is the Network layer, which provides switching and routing criteria, including the establishment and use of IP addresses. In a preferred embodiment of the present invention, the Ethernet switch, under the control of the management module, performs Layer 3 packet filtering by comparing the IP address of the responding DHCP server with those IP addresses listed in the list of trusted DHCP servers. Preferably, this list is maintained in the management module, or alternately in the Ethernet switch.

[0020] If the responding DHCP server is on the list of trusted servers, then the DHCP OFFER message from the responding DHCP server is allowed to pass to the requesting server blade, which selects one of the PXE servers from the listing in the DHCP OFFER message, and sends a request to a selected PXE server for a boot program (block 308), which is then downloaded into the server blade.

[0021] If the responding DHCP server is NOT on the list of trusted servers, then the management module blocks the OFFER message from passing through the Ethernet switch to the server blade that made the request (block 310). The network and/or system administrator is notified (block 312) of the presence of an unauthorized DHCP server on the network. Preferably, this message is sent as a Simple Network Management Protocol (SNMP) trap or alert and to the management module, which can forward the alert to additional consoles on a management module network (not shown).

[0022] A query (block 314) is then made to determine if the server blade should download a boot program from a trusted PXE server on a secure local area network (LAN). If so, then such a download is performed (block 315); if not, then the process continues (block 313) until a trusted DHCP response is received, resulting in the server blade continuing in a network boot. Otherwise, the process ends, resulting in the server blade booting from another non-network local device or means (not shown).

[0023] After the server blade has booted up, a second request is sent out to the network requesting a DHCP set-up (block 316). A DHCP set-up provides configuration parameters to the server blades. DHCP is an extension of BOOTP, an IP allocation specification. DHCP supports the concept of a “lease” of an IP address, in which a DHCP server allocates an IP address to the server blade for a pre-determined period of time. The server blade broadcasts a DHCPDISCOVER packet to the network of DHCP servers. DHCP servers on the network see the broadcast and return a DHCPOFFER packet that contains an offered IP address for the blade server and other information (block 318). The DHCP servers conduct preliminary testing before offering the addresses, such as determining if the offered IP address is already in use by another node on the network. Typically, the server blade chassis (via the Ethernet switch) will receive multiple DHCPOFFER packets from different DHCP servers.

[0024] The Ethernet Switch 216 then compares the IP address of the responding DHCP server, found in the DHCPOFFER packet, with the list of trusted DHCP servers managed by the management module (block 320). If the DHCPOFFER is from a valid DHCP server, the Ethernet switch 216 selects one of the DHCPOFFER packets based on some predetermined criteria, such as which packet was received first, which packet offers the longest lease, or which DHCP server provides the most information that the specific server blade needs for optimal operation, and passes the selected packet to the appropriate server blade. After selecting the preferred DHCP packet, the server blade sends out a DHCPREQUEST packet to the selected DHCP server. Assuming that the offer is still valid, the chosen DHCP server then returns a DHCPACK acknowledgment packet that tells the server blade that the lease is finalized (block 328), turning over ownership and maintenance of the lease to the server blade.

[0025] If the DHCPOFFER is from an unauthorized DHCP server, DHCP controlled IP address allocation and set-up is blocked (block 322) and the administrator is notified, via an SNMP trap or via the Management Module interface, of the presence of an unauthorized DHCP server on the network (block 324). A choice is then made (decision block 326) as to whether a DHCP controlled IP address set-up should be performed using a trusted DHCP server on a local secure LAN (block 330).



[0026] In another preferred embodiment, an information technology (IT) service organization is used to coordinate alternate types of PXE servers. Unlike DHCP, a limitation of the PXE protocol is that more than one PXE server in a network causes chaos due to the lack of ability in the PXE client to determine what server is the preferred server. Referring now to **Figure 4**, there is illustrated a block diagram of a PXE network **400** having an IT service organization, such as IBM's Global Services (IGS) that manages various deployment server types, such as Remote Deployment Manager (RDM) PXE server **402**, Linux® PXE server **404**, and Windows® 2000 Remote Installation Services (RIS) PXE server **406** for contracted accounts. The IT service organization **408** assigned systems administrator maintains a list **410** of trusted PXE boot program servers, which allows the same IT service organization **408** assigned systems administrator to manage the various deployment server types, maintain the permission lists for each PXE boot program server type, monitor the network for unauthorized DHCP/PXE servers, and shut down network ports of the unauthorized DHCP/PXE servers. Use of the aforementioned embodiments allow the IT service organization **408** to manage various PXE servers and to have them coexist in the same network, and thus reducing supports costs created by the consolidation of network and support organizations, since the permission list for each chassis can control where each blade chassis obtains its boot image.

[0027] It should be noted that this invention is possible due to the tight integration of the Management Module, Ethernet Network Switch, and the actual server blades within the server blade chassis. Because of this tight integration, this invention does not require any code changes to the blade firmware, so the invention is agnostic to the vendor of BIOS on the blade.

[0028] It should be understood that at least some aspects of the present invention may alternatively be implemented in a program product. Programs defining functions on the present invention can be delivered to a data storage system or a computer system via a variety of signal-bearing media, which include, without limitation, non-writable storage media (e.g., CD-ROM), writable storage media (e.g., a floppy diskette, hard disk drive, read/write CD ROM, optical media), and communication media, such as computer and telephone networks including Ethernet.

It should be understood, therefore in such signal-bearing media when carrying or encoding computer readable instructions that direct method functions in the present invention, represent alternative embodiments of the present invention. Further, it is understood that the present invention may be implemented by a system having means in the form of hardware, software, or a combination of software and hardware as described herein or their equivalent.

**[0029]** While the invention has been particularly shown and described with reference to a preferred embodiment, it will be understood by those skilled in the art that various changes in form and detail may be made therein without departing from the spirit and scope of the invention.